



**University of Rome Tor Vergata**  
Bachelor science degree in Engineering Sciences

# **DESIGN AND REALIZATION OF A KINEMATIC INTERFACE FOR MUSIC SYNTHESIS: A LOW-COST OPTICAL BASED THEREMIN**

**ANDREA LOMUSCIO**

**SUPERVISOR: PROF. CORRADO DI NATALE**

**CO-SUPERVISOR: ING. ALEXANDRO CATINI**

# **THEREMIN**


**Invented in Russia in 1919**

**by Lev Sergeevič Termen (aka Léon Theremin)**



# **OUR PROJECT**

**Build a low-cost Theremin replica using a  
completely different working principle.**




**Better!**


**Smaller**

**Cheaper**


# HOW A REAL THEREMIN WORKS? LC CIRCUIT SINE WAVE




# VARIABLE CAPACITOR USING HAND + ANTENNA AS PLATES




# HEARING RANGES




# HETERODYNE





# HETERODYNE




# SHARP IR DISTANCE RANGE SENSORS




# TRIANGULATION




# TRIANGULATION





# SHARP IR DISTANCE RANGE SENSORS






MCP3008






**7€ each**




2€




Analog audio output

**starts from  
20€**



MCP3008



**7€ each**

**2€**

**starts from  
20€**

# MOOG ETHERWAVE THEREMIN

**Starts from 370€**

**Save up to 330€**







**V<sub>out</sub> (analog)**




**10bit digital signal**




# MCP3008

**8-channel, 10 bit ADC converter,  
SPI interface, up to 200ksamples/second**




# SPI



## Serial Peripheral Interface communication bus



# MCP3008 + RASPBERRY PI

## Wiring Diagram





# WHAT'S HAPPENING INSIDE THE RASPBERRY?



# WHAT'S HAPPENING INSIDE THE RASPBERRY?



# WHAT'S HAPPENING INSIDE THE RASPBERRY?



OSC  
open sound control

# THE PYTHON CODE

```
# import some external libraries
import spidev
import time
import os
import OSC

# initialize the SPI bus
spi = spidev.SpiDev()
spi.open(0,0)

# read SPI data from MCP3008 chip
def readadcadcnum):
    r = spi.xfer2([1,(8+adcnum)<<4,0])
    adcout = ((r[1]&3) << 8) + r[2]
    return adcout

# we define the input channels
adc_vol = 1
adc_note = 0

# start OSC Server
client = OSC.OSCClient()
client.connect('127.0.0.1', 9001)

# main loop
while True:


    # reading values from sensors
    note = readadcadc_note)
    vol = readadcadc_vol)

    # send a OSC message
    client.send(OSC.OSCMessage("/osc", [vol,note]))
```

# WHAT'S HAPPENING INSIDE THE RASPBERRY?



# THE PURE DATA PATCH



# FUTURE IMPLEMENTATIONS




# **AUTO-TUNE FUNCTION**

**here's why you'll love this theremin**


# AUTO-TUNE FUNCTION

C Major Key




# AUTO-TUNE FUNCTION

D Major Key example




# AUTO-TUNE FUNCTION

Custom configuration example




# AUTO-TUNE EXAMPLE

Blues in C key




77







# PITCH ONLY MODE





# CHANGE WAVEFORM FROM SINE TO SAWTOOTH






ELEKTRA  
BECKUM  
200






# VOLUME SENSOR NOW CONTROLS VIBRATO EFFECT











**Waveform Knob**

**Playing-mode Knob**







**THANK YOU FOR YOUR ATTENTION**